



Dimensions				Abbreviation for		Load ratings [kN]				Speed limits	Weight
d	D*	B	r <sub>s</sub> min	Shields	Seals	Bearing		Pulley			
						dyn.	stat.	dyn.	stat.	min <sup>-1</sup>	kg
mm						C	C <sub>0</sub>	C	C <sub>0</sub>		
10	32	14.0	0.6	LZ3200BZZRSTNG LB3200BZZRSTNG	LZ3200BZRSRSTNG LB3200BZRSRSTNG	7.8	4.55	7.45	4.15	16,000	0.061
12	35	15.9	0.6	LZ3201BZZRSTNG LB3201BZZRSTNG	LZ3201BZRSRSTNG LB3201BZRSRSTNG	10.6	5.85	9.95	5.20	15,000	0.079
15	40	15.9	0.6	LZ3202BZZRSTNG LB3202BZZRSTNG	LZ3202BZRSRSTNG LB3202BZRSRSTNG	11.8	7.10	11.00	6.45	13,000	0.100
17	47	17.5	0.6	LZ3203BZZRSTNG LB3203BZZRSTNG	LZ3203BZRSRSTNG LB3203BZRSRSTNG	14.6	9.00	13.80	8.30	10,000	0.165
20	52	20.6	1.0	LZ3204BZZRSTNG LB3204BZZRSTNG	LZ3204BZRSRSTNG LB3204BZRSRSTNG	19.6	12.50	18.30	11.00	9,000	0.210
25	62	20.6	1.0	LZ3205BZZRSTNG LB3205BZZRSTNG	LZ3205BZRSRSTNG LB3205BZRSRSTNG	21.2	14.60	19.90	13.40	8,000	0.330
30	72	23.8	1.0	LZ3206BZZRSTNG LB3206BZZRSTNG	LZ3206BZRSRSTNG LB3206BZRSRSTNG	30.0	21.20	27.90	18.60	7,100	0.500
35	80	27.0	1.0	LZ3207BZZRSTNG LB3207BZZRSTNG	LZ3207BZRSRSTNG LB3207BZRSRSTNG	39.0	28.50	36.20	25.0	6,300	0.660

\* with spherical outer ring D 0.05 mm